

# AK-Nord



## SER2USB – CABLE (SERIAL)

Adapter to connect printers and multifunctional devices with a USB connection to the COM interface.



### Current supply

Power supply unit:  
100-240 V / 50/60 Hz  
Output:  
5 volts / about 100 mA

### USB interface

USB1.0 Low-Speed  
USB1.1 Low/Full-Speed  
USB2.0 Low/Full-Speed

### Serial interface plug

9-pole SUB-D connector

## LPT2USB – CABLE (PARALLEL)

Adapter to connect printers and multifunctional devices with a USB connection to the LPT interface.



### Current supply

Power supply unit: 100-240 V / 50/60 Hz  
Output: 5 volts / about 100 mA

### USB interface

USB1.0 Low-Speed  
USB1.1 Low/Full-Speed  
USB2.0 Low/Full-Speed

### LPT interface

01 Unidirectional  
02 Bi-directional  
03 1284.4 Bi-directional

## XT-MICRO-SXL-C

The XT-Micro serves to integrate printers or any parallel terminals to the network.



Due to its small dimensions, the XT-Micro is especially suitable for installation solutions into existing terminals.

### Current supply

Power supply unit: 5 Volt / ca. 850 mA

### Temperature range

-40°C .. + 70°C

### Dimensions

45 x 48 x 14 mm

### Centronics IEEE1284

26-pin plug