

DEGSON Din Rail Terminal Blocks: The All-in-One Solution for Industrial Connectivity

I. Why the Demand for Din Rail Terminal Blocks is Surging? Industrial Evolution Drives a Connectivity Revolution

Amid the global wave of industrial automation and digitalization, efficient and reliable power/signal transmission has become the "lifeline" of modern manufacturing. According to McKinsey research, equipment downtime caused by connection failures costs industries \$50 billion annually. Traditional terminal blocks, plagued by complex installation and poor environmental adaptability, struggle to meet the evolving demands of critical scenarios:

Industrial Automation: Robotic production lines and PLC control cabinets require rapid deployment and vibration-resistant connections.

Renewable Energy Systems: Photovoltaic inverters and energy storage systems demand high-temperature-resistant, corrosion-proof outdoor solutions.

Rail Transit: Train control systems require DNV Class certification to withstand high-salinity, high-vibration environments.


Petrochemicals: Explosion-proof scenarios mandate strict fire and arc-resistant performance.

With **modular design, full-scenario adaptability, and efficiency**, DEGSON Din Rail Terminal Blocks have become the benchmark for Industry 4.0 connectivity, achieving over 30% annual growth and serving premium markets across 50+ countries.


II. DEGSON Din Rail Terminal Block Portfolio: Precise Matched for Diverse Applications

1. By Connection Technology


DS Push-in Terminals: Tool-free, one-click installation boosts wiring efficiency by 70%, ideal for equipment debugging with frequent line changes.




WS/STB Spring-Clamp Terminals: Self-locking spring mechanisms excel in high-vibration environments like rail transit and heavy machinery.



PC Copper Screw Terminals & DC Steel Screw Terminals: Copper handles high currents (up to 150A), while steel resists corrosion for harsh environments (e.g., petrochemicals, marine).



DHV KV Screw Terminals: Ultra-high-voltage design (1000V+) for renewable energy busbars.



2. Industry-Specific Solutions

Application	Recommended Series	Key Advantages
Industrial Robotics	WS Spring-Clamp	10G vibration resistance, 500K cycles
Solar Inverters	PC Copper Screw	105°C tolerance, IP67 protection
Marine Power Systems	DC Steel Screw	DNV-certified, 2000hr salt spray test
Explosion-Proof Cabinets	DHV KV Screw	UL94 V-0 flame retardant, arc-proof

III. Five Core Advantages of DEGSON Din Rail Terminal Blocks

1. Rapid Installation, Doubled Efficiency

Push-in Technology: Supports 0.2-6mm² wires without tools (<3 seconds per connection), saving 80% time vs. screw terminals.

Dual Spring Design: Maintains consistent contact pressure, eliminating loose connections from manual tightening.

2. Conquering Extreme Environments

Wide Temperature Range: Operates reliably from -40°C to 105°C, from Arctic sites to desert power plants.

Chemical Resistance: PA66+30% glass fiber housing withstands acids, alkalis, and oils, extending lifespan to 15+ years.

3. Global Compliance, Trusted Safety

Certifications: UL, IEC, CE, RoHS/REACH compliant for global market access.

Rigorous Testing: DNV-certified salt spray, vibration, and shock tests ensure zero failures in marine/rail applications.

4. Lifecycle Cost Optimization

Maintenance-Free: Anti-oxidation plating and self-cleaning contacts reduce downtime.

- **Modular Expansion:** Din rail compatibility simplifies system upgrades, cutting redundant costs.

5. Sustainable Future

100% recyclable materials, 30% lower carbon footprint, supporting ESG goals.

IV. How to Choose the Right Din Rail Terminal Block? A 3-Step Guide

Step 1: Define Electrical Parameters

Voltage: $\leq 300\text{V}$ control circuits → WS Series; $\geq 600\text{V}$ → DHV KV Series.

Current:

$\leq 10\text{A}$: Push-in terminals (cost-effective).

$\geq 50\text{A}$: PC Copper Screw terminals (optimal).

Step 2: Assess Environmental Risks

Vibration/Shock: Spring-clamp (WS/STB) > Screw > Push-in.

Corrosion: DC Steel Screw > Nickel-plated Copper > Standard Copper.

Temperature Extremes: PC Copper or DHV KV for 105°C environments.

Step 3: Match Connection Needs

Rapid Deployment: Push-in terminals ($0.2\text{-}4\text{mm}^2$ wires).

High-Density Layout: 6mm compact design saves 40% Din rail space.

Smart Features: Add DEGSON LED-indicator modules for real-time status monitoring.

V. DEGSON's Innovation Pledge: Redefining Industrial Connectivity

Facing carbon neutrality and digital twin challenges, DEGSON drives R&D breakthroughs:

- **Smart Integration:** Current/temperature sensors enable real-time diagnostics.
- **Ultra-High Voltage:** 2000V terminals for next-gen energy storage and ultra-fast charging.
- **Green Manufacturing:** 100% renewable materials and zero-carbon production by 2030.

Choosing DEGSON Din Rail Terminal Blocks isn't just selecting a product—it's committing to efficiency, safety, and a sustainable future.
